



## MileGuard<sup>®</sup> GF-4 Motor Oils

**MileGuard GF-4 Motor Oils** are superior-quality, high detergent automotive engine oils specially formulated to meet the stringent lubrication requirements of today's engines. High viscosity index Group II base oils combine with a carefully selected additive package to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits.

**MileGuard GF-4 Motor Oils** meet or exceed the requirements of MIL-L-46152E, Ford WSS-M2C153-H and WSS-M2C930-A (SAE 5W-20) and WSS-M2C929-A (SAE 5W-30)

Meets DaimlerChrysler DC MS10797 (SAE5W-20), DC MS10796 (SAE 5W-30) and DC MS10798 (SAE 10W-30) specifications.

Meets Honda Service Fill Specifications.

Meets GM 6094M specification (SAE 5W-20, SAE 5W30 and SAE 10W30)

Meets Toyota Specifications.

Meets API Service Category SM, SL, SJ, SH complies with ILSAC GF-4 requirements.

MileGuard GF-4 Motor Oils			
SAE Grade	5W-20	5W-30	10W-30
API Gravity @ 60°F	32.2	29.9	29.1
Sp. Gr. @ 60°F	.8637	.8767	.8811
Flash, COC, °F	428	420	405
Pour Pt., °F	-35	-30	-30
Viscosity, cSt @ 40°C	47.4	66.5	76.3
Viscosity, cSt @ 100°C	8.1	10.5	11.2
Viscosity Index	142	150	135
Zinc, Wt. %	0.0845	0.0845	0.0845
API Service Category	SM	SM	SM
ILSAC	GF-4	GF-4	GF-4



**Warren Oil Company, Inc**

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301