



## MileGuard<sup>®</sup> Multi-Purpose ATF

**MileGuard Multi-Purpose ATF** is a multi-purpose automatic transmission fluid (ATF) and is recommended as a replacement fluid for automatic transmissions meeting original equipment manufacturer's (OEM) performance requirements of General Motors, Ford, and other domestic and imported passenger cars, vans and light trucks where Dexron II, Dexron II-E, Dexron III-G, Dexron III, H Revision, Automatic Transmission Fluid, or Ford Mercon fluids are specified. It is also recommended for Detroit Diesel Allison C-3, C-4 applications, and Caterpillar TO-2 applications.

**MileGuard Multi-Purpose ATF** is suitable for most power steering units. Other manufacturer suggested applications include mobile hydraulic and industrial systems, and rotary air compressors under certain service conditions.

### Benefits

- Excellent low temperature fluidity for good cold-start shifting
- Resistance to foaming
- Oxidation and thermal stability for long life
- Protection against rust, corrosion and wear
- Multiple approvals for lower inventory requirements
- Compatible with all transmission seal material

**MileGuard Multi-Purpose ATF** is not for use in vehicles requiring Ford Type F, Mercon V, Chrysler ATF fluids, or Dexron VI. Not for use in 6-speed or continuously variable transmissions. Always check your owner's manual for proper application



**Warren Oil Company, Inc**

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



## MileGuard<sup>®</sup> Multi-Purpose ATF

### Typical Characteristics

<b>MileGuard Multi-Purpose ATF</b>	
Appearance	Red, Dyed
Viscosity	
@ 40 °C, cSt	33.37
@ 100 °C, cSt	6.87
Viscosity Index	161
Pour Point, °F	-40
Flash Point COC, °F	405
Dexron III G	Y
Dexron III H	Y
Mercon	Y
Allison C-4	Y
Cat TO-2	Y



**Warren Oil Company, Inc**

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:  
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301